



Equipped with:

- Hydraulic sliding linkage
- Adjustable belt-tensioner
 - Adjustable rear roller



Inner lining



Rotor bearing internally fitted



Pto shaft with overrun clutch

SHREDDERS FOR GRASS, TWIGS, SET-ASIDE, etc. (Ø max 6 cm)



Technical data

| Model | Cutting width | Weight | Tractor | Pto | Rotor | Overall width | Blade tip speed |
|--------|------------------|--------|------------|-----|-------|------------------|--------------------|
| | m | Kg | HP min/max | Rpm | Rpm | m | m/sec |
| MC 180 | 1,80 | 545 | 55/70 | 540 | 2150 | 1,97 | 49 |
| MC 210 | 2,10 | 580 | 70/80 | 540 | 2150 | 2,27 | 49 |

Machines

| Model | No of flails |
|--------|------------------|
| MC 180 | 12 hammer blades |
| MC 210 | 12 hammer blades |

Warning

Suitable for tractors equipped with one double acting valve

IT IS RECOMMENDED that the connection between tractor and shredder and its setting up should be made with the Dealer according the instructions and warnings listed on our Use and Maintenance Manual. For further information please contact our after sales service.

| Working positions (m) | | | | |
|--------------------------|---------------------|--|--|--|
| MC 180 | 0,83 0,97 0,28 1,52 | | | |
| MC 210 | 0,83 1,27 0,28 1,82 | | | |

Interchangeable on the same rotor Hammer blades for: grass, twigs. Ø max 6 cm Kit multi-use blades for: grass, twigs, straw, setaside, etc. Ø max 4 cm Cod. 0901016 Cod. 0901085 Cod. 0901086